

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 August 2004 (26.08.2004)


PCT

(10) International Publication Number
WO 2004/072570 A1

- (51) International Patent Classification⁷: **F28F 3/08**, (74) Agents: **BERGLUND, Stefan et al.**; Bjerkéns Patentbyrå KB, Östermalmsgatan 58, S-114 50 Stockholm (SE).
- (21) International Application Number: **PCT/SE2004/000138**
- (22) International Filing Date: 2 February 2004 (02.02.2004)
- (25) Filing Language: **Swedish**
- (26) Publication Language: **English**
- (30) Priority Data: **0300364-7** 11 February 2003 (11.02.2003) **SE**
- (71) Applicant (for all designated States except US): **ALFA LAVAL CORPORATE AB [SE/SE]**; P.O Box 73, S-221 00 Lund (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **BLOMGREN, Ralf [SE/SE]**; Älgvägen 13, S-239 34 Skanör (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: A PLATE PACK, A PLATE HEAT EXCHANGER, AND A PLATE MODULE



(57) Abstract: The invention refers to a plate package and a plate heat exchanger. The plate package includes plate modules with two heat exchanger plates (3), which extend at at least an intermediate plane, an upper plane and a lower plane. The heat exchanger plates are permanently connected to each other and form an inner first space therebetween. The plate modules are stacked to each other and form a second space therebetween. Each heat exchanger plate includes two portholes (13) which permit communication with the first space. Each porthole is defined by a port edge (31) and surrounded by a ring groove (32) for a gasket member at a distance from the port edge. The ring groove is formed by a bottom (33) at the level of the intermediate plane, an inner lateral limitation (34) extending upwardly from the bottom towards the port edge, and an outer lateral limitation (35) extending upwardly from the bottom away from the port edge. The outer lateral limitation forms a surface extending without any interruptions continuously around the bottom whereas the inner lateral limitation has a discontinuous extension around the bottom and includes interruptions along this extension.

WO 2004/072570 A1